



RIG INVENTORY & SPECIFICATIONS

RIG TWO 17 LOADS (WITHOUT BOILER)

Depth capacity: TVD 2800m, MD 4500+ m

MAST
MAKE/TYPE Rostel Industries/Telescoping Double - Free Standing
CLEAR HEIGHT 30.50m (100')
CAPACITY Static Hook Load: 125,000 daN (281,000 lbf) w/8 lines Setback Capacity: 3400m - 180 stands of 101.6mm (4') X95 Drill Pipe Wind Capacity: 135 km.h (84 m/h) w/Full Set Back & No hook Load

SUBSTRUCTURE
MAKE/MODEL Rostel Industries/ Stepdown
DIMENSIONS (L X W X H) 12.2m x 4.12m x 3.84m (40' x 13.5' 12.6')
KELLY BUSHINGS/ROTARY TABLE BEAM TO GROUND 4.30m (14.11')/3.50m (11.48')
CASING CAPACITY 88,960 daN (199,990 lbf) w/77,840 daN (174,990 lbf) Simultaneous Setback

DRAWWORKS
MAKE/MODEL Rostel Industries/R500
BRAKE Eaton 224mm Disc
POWER Detroit Diesel, Series 60 14L, Input Power 350kW (630hp)
TRANSMISSION Allison, S6610H
ROTARY TABLE MAKE/SIZE Continental Emsco/ 17.5" (444.5mm)

OVERHEAD
TRAVELLING BLOCK/HOOK McKissick 150/BJ-6150 150 (133,447 daN)
KELLY 89mm (3.5") x 12.20m (40') Square, w/Foster Model 77 Spinner

PUMP ONE
MAKE/MODEL JJ/F1000 Triplex

PUMP TWO
MAKE/MODEL JJ/F800 Triplex

MUD SYSTEM
SHAKER Derrick FLC 500 Shale Shaker
CAPACITY Single Tank (Three Compartments) 1. Shaker 20 m3 (5,280 gal) 2. Settling 20 m3 (5,280 gal) 3. Suction 20 m3 (5,280 gal)

WELL CONTROL
228.6mm (9") BOPs *Note: Other Configurations Available Upon Request*

TUBULARS
SURFACE COLLARS 2 X 203.2mm (8") or 228.6mm (9")
DRILL COLLARS 16 x 158mm (6.25"), ID 59mm (2.33"), 114mm (4.5") XH Slip Recessed & Hardbanded
HEVI-WEIGHT 50 x 102mm (4")
DRILL PIPE 300 x 102mm (4") *Note: Other Pipe Available Upon Request*

HEAD OFFICE & OPERATIONS
BOX 2189, 490 Canal Street, Brooks, AB T1R 1C8
P 403-793-2092 F 403-793-2094 TF1-888-869-5324

CONTRACTS OFFICE
700, 435 - 4TH Avenue SW, Calgary, AB T2P 3A8
P 403-269-2041 F 403-269-2652

www.excaliburdrilling.com